



Hydraulic Super Delux Emergency Recovery Trolley (UMS-HR406)

Technical Specifications

	1710	1710A
Overall Approximate Dimension*	1910 mm x 710 mm, 75" x 28" (L x W)	1910 mm x 855 mm, 75" x 34" (L x W)
Stretcher Dimension*	1825 mm x 560 mm, 72" x 22" (L x W)	1825 mm x 710 mm, 72" x 28" (L x W)
Mattress Platform Dimension*	1790 mm x 560 mm, 70" x 22" (L x W)	1790 mm x 710 mm, 70" x 28" (L x W)
Backrest**	0°- 65°	0°- 65°
Trendelenburg**	0°-18°	0°-18°
Reverse Trendelenburg**	0°- 6°	0°- 6°
Minimum Height*	675 mm, 27"	675 mm, 27"
Maximum Height*	925 mm, 36"	925 mm, 36"
Safe Working Load	165 kgs	165 kgs
Patient Weight Bearing Capacity ¹	135 kgs	135 kgs

Add on Accessories

- Resine covered mattress of 50 mm (2") thickness, 1710 (1752D), 1710A (1752F)

Safety Standards

- Compliance for safety: International Standards IEC 60601-2-52

Standard Features

- Two section top with removable X-ray permeable stretcher
- Gas spring assisted trendelenburg and reverse trendelenburg positions
- Height adjustment by foot operated high quality hydraulic pump
- Raised backrest on ratchet
- 50 mm thick mattress
- Buffers at 4 corners (135 mm)
- High grade synthetic body castor wheels (125 mm) two with brakes and two without brakes
- Synthetic rubber covered push-pull handle
- Sliding X-ray cassette holder
- Stainless steel telescopic IV pole along with provision at 4 positions
- Pretreated and epoxy powder coated
- Swing away type stainless steel side rails
- Safety belts



Cardiac Trolley (UMS-HC406)

- Luxurious hydraulic stretcher trolley with adjustable back rest, knee rest, trendelenburg, reverse trendelenburg & adjustable height.
- Back Rest adjustable by gas spring, knee rest adjustable by super smooth crank, other functions adjustable by hydraulic mechanism
- Size: 2082L X 650W X 600 TO 900 HI-L0 POSITION
- Framework made of mild steel epoxy coated finish with X-ray permeable acrylic Top
- Collapsible Stainless Steel side railings
- Equipped with hydraulic pump
- Equipped with I.V. Pole, drainage hook & bumper protection
- 150mm dia noiseless castors with simultaneous braking system which locks / unlocks 2 castors with single pedal press
- International quality structure and functionality to satisfy the needs of the best hospital and Operation theaters

