



Bed Positions

Height Adjustable Position

Trendlenburg Position

Head and Foot Position

**FUTURA DELUX MANUALLY (5) FUCTION ICU BED UMS -MD5**

Technical features		Standard configuration
Bed structure material	MS tube 25x75 pipe 1.4 mm thickness and 1.25 mm thickness CRC sheet with perforated copper wire c02 welding	(1)Head position up down (2) foot position up down (3) height hi lo position (4) UP tredelenburg angle (5) reverse tredelenburg angle
Structure material	MS tube pipe 1.4 mm and 1.25 mm CRC sheet	ABS Moulded panels
Overall bed outer damnation	2100L X980W	ABS 4pis tuck away safety side railing
Mattress platform damnation	2000L X 880W	125 mm castor wheel with 2 brake
Height adjustment	450 to 750 mm electronic pillar through	MS CRC perforated sheet
Reveres trengle	Hand key through	Manually operating polymer handle systems through
Up trengle	Hand key through	4 wheel With 2 brake systems
Operating systems	4 hand key through	4 side bed safety side wafer
Product finis	Pre-treated and epoxy powder coated	4 side iv pole hole
Safe working load	200 kg	Mattress IV stand cylinder trolley optional



### FUTURA SEMI DELUX MANUALLY (5) FUCTION ICU BED UMS -MD6

Technical features		Standard configuration
Bed structure material	MS tube 25x75 pipe 1.4 mm thickness and 1.25 mm thickness CRC sheet with perforated copper wire c02 welding	(1)Head position up down (2) foot position up down (3) height hi lo position (4) UP tredelenburg angle (5) reverse tredelenburg angle
Structure material	MS tube pipe 1.4 mm and 1.25 mm CRC sheet	ABS Moulded panels
Overall bed outer damnation	2100L X980W	Alluminum collapsible safety side railing
Mattress platform damnation	2000L X 880W	125 mm castor wheel with 2 brake
Height adjustment	450 to 750 mm electronic pillar through	MS CRC perforated sheet
Reveres trengle	Hand key through	Manually operating polymer handle systems through
Up trengle	Hand key through	4 wheel With 2 brake systems
Operating systems	4 hand key through	4 side bed safety side wafer
Finice epoxy powder coated	Powder coated	4 side iv pole hole
Safe working load	200 kg	Mattress IV stand cylinder trolley optional



**FUTURA MANUALLY STD (5) FUCTION ICU BED UMS -MD7**

Technical features		Standard configuration
Bed structure material	MS tube 25x75 pipe 1.4 mm thickness and 1.25 mm thickness CRC sheet with perforated copper wire c02 welding	(1)Head position up down (2) foot position up down (3) height hi lo position (4) UP tredelenburg angle (5) reverse tredelenburg angle
Structure material	MS tube pipe 1.4 mm and 1.25 mm CRC sheet	Deluxe steel panel
Overall bed outer damnation	2100L X980W	Alluminum collapsible safety side railing
Mattress platform damnation	2000L X 880W	125 mm castor wheel with 2 brake
Height adjustment	450 to 750 mm electronic pillar through	MS CRC perforated sheet
Reveres trengle	Hand key through	Manually operating polymer handle systems through
Up trengle	Hand key through	4 wheel With 2 brake systems
Operating systems	4 hand key through	4 side bed safety side wafer
Finice epoxy powder coated	Powder coated	4 side iv pole hole
Safe working load	200 kg	Mattress IV stand cylinder trolley optional